



FEATURES

Max absorbed power: 50 W
Air flow (max): 100 m³/h
Max air speed: 1,13 m/s
Max power noise level: 61 dB(A)
Water tank capacity: 1,1 l
Swing function



COMPACTNESS

The space-saving more compact.



OPENABLE TANK

Easy accessible water tank.



FILTER

Fabric Antidust filter.



SILENT SYSTEM



		PELER 1
Product code		99467
Power supply	V/ph/Hz	220-240 / 1 / 50
Maximum power absorption	W	50
Stand-by power consumption	W	0,2
Fan speeds	n	3
Air volume (maximum)	m ³ /h	100
Air speed (maximum)	m/s	1,13
Sound pressure level (1)	dB (A)	44 - 43
Maximum Sound power level (1)	dB (A)	61
Degrees of protection provided by enclosures		-
Insulation class		II
Power cable	n / mm ²	2 x 0,75
Water tank capacity	l	1,1
Evaporative sheet		cloth
Control panel		LED
Maximum remote control range (distance / angle)	m / °	-
Conformity Mark		CE
Certification Mark		Intertek - GS
Product size (W x H x D)	mm	190x500x190
Gift box size (W x H x D)	mm	210x550x210
Weight (without packing)	kg	2,7
Weight (with packing)	kg	3,5
Units per master box	n	6
Master size (W x H x D)	mm	652x570x438
Timer		1, 2 or 4 hours
Removable water tank		-
Oscillating function		YES of base
Remote controller		-
Ionizer		-
Wall support		-
Power supply cable housing		-

(1) TEST CONDITIONS: The sound pressure level is measured in half-anechoic room far 2 meters from the front of the appliance with the microphone at 1 meter of height. During the test, all the appliance functions are enabled with the exception of swing function (if available)