

NEW

CALDO POCKET

The most compact fan heater yet

Cod. 99229



COMPACT TECHNOLOGY

Small, practical and compact, with pull-out feet, it fits seamlessly into any setting.



3 MODES OF USE

Fan only and two power levels, for customised comfort



ANTI-FROST FUNCTION

To set automatic ignition, when the temperature drops below 5°C



1500W WITH CERAMIC TECHNOLOGY

The ceramic resistance guarantees more even and constant heat distribution.

FEATURES

- Max thermal power: 1500 W
- 2 power levels (1000 W - 1500 W)
- Ceramic heating element
- Room thermostat
- Safety thermostat
- Overheating protection
- Anti-tip switch
- Fan-only function
- Anti-freeze function
- Mechanical controls
- Pull-out feet and convenient handle



Technical specifications ceramic fan heaters

		NEW			NEW	
		CALDO POCKET	CALDODESIGN	CALDODESIGN O	CALDODESIGN S	CALDO CUBIC
PRODUCT CODE		99229	99447	99402	99404	99228
EAN CODE		8021183992298	8021183994476	8021183994025	8021183994049	8021183992281
Thermal power (Max)	W	1500	1800	1800	1800	1800
Power settings		ONLY FAN / 1000 / 1500	ONLY FAN / 1000 / 1800	ONLY FAN / 1000 / 1800	ONLY FAN / 1000 / 1800	ONLY FAN / 900 / 1800
Heating volume (max)	m ³	50	55	55	55	55
Dimensions (WxHxD)	mm	159 x 219 x 98	245 x 248 x 216	245 x 248 x 216	245 x 248 x 216	165 x 215 x 145
Gift box dimensions (WxHxD)	mm	169 x 240 x 106	275 x 275 x 235	275 x 275 x 235	275 x 275 x 235	183 x 230 x 183
Master dimensions (W x H x D)	mm	552 x 495 x 180	750 x 290 x 570	750 x 290 x 570	750 x 290 x 570	378 x 247 x 378
Units per master		10	6	6	6	4
Weight (without packaging)	kg	1,1	1,8	1,8	1,8	1,6
Weight (with packaging)	kg	1,2	2,2	2,2	2,2	1,8
Insulation class		II	II	II	II	II
Degree of protection provided by covers		IPX0	IP X0	IP X0	IP X0	IP21
Electrical power supply	V-F-Hz	220/240 - 1 - 50/60	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50/60
Conformity mark		CE	CE	CE	CE	CE
Ceramic resistance		√	√	√	√	√
Timer		-	-	-	-	-
Room thermostat		√	√	√	√	√
Safety thermostat		√	√	√	√	√
Ventilation function		√	√	√	√	√
Oscillating function		-	-	-	-	-
Anti-tip switch		√	-	-	-	√
Anti-ice function		√	√	√	√	√
Power selector		√	√	√	√	√
Eco Function		-	-	-	-	-
Remote control		-	-	-	-	-
Tilt adjustment		-	√	√	√	-
LED indicators		-	√	√	√	√
Integrated wi-fi & voice control		-	-	-	-	-

		CALDO TRENDY	CALDO TRENDY ST	CALDO TRENDY T	CALDO SKY B WIFI	CALDO SKY G WIFI	CALDO UP T
PRODUCT CODE		99268	99267	99266	99264	99265	99364
EAN CODE		8021183992687	8021183992670	8021183992663	8021183992649	8021183992656	8021183993646
Thermal power (Max)	W	1800	2000	2000	2000	2000	2000
Power settings		900 / 1800	1000 / 2000	1000 / 2000	ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000
Heating volume (max)	m ³	55	60	60	60	60	60
Dimensions (WxHxD)	mm	216 x 284 x 125	190 x 450 x 140	241 x 604 x 190	550 x 180 x 127	550 x 180 x 127	560 x 185 x 145
Gift box dimensions (WxHxD)	mm	262 x 316 x 150	232 x 486 x 183	278 x 655 x 225	598 x 220 x 156	598 x 220 x 156	595 x 225 x 170
Master dimensions (W x H x D)	mm	465 x 647 x 277	387 x 511 x 250	465 x 670 x 293	610 x 330 x 460	610 x 330 x 460	605 x 355 x 470
Units per master		6	2	2	4	4	4
Weight (without packaging)	kg	1,7	2,5	3,2	2,3	2,3	2,8
Weight (with packaging)	kg	2,0	3,0	3,8	3,0	3,0	3,1
Insulation class		II	II	II	II	II	II
Degree of protection provided by covers		IP21	IPX0	IPX0	IP22	IP22	IP X0
Electrical power supply	V-F-Hz	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50
Conformity mark		CE	CE	CE	CE	CE	CE
Ceramic resistance		√	√	√	√	√	√
Timer		√	√	√	√	√	√
Room thermostat		√	√	√	√	√	√
Safety thermostat		√	√	√	√	√	√
Ventilation function		-	-	-	√	√	√
Oscillating function		√	√	√	√	√	√
Anti-tip switch		√	√	√	-	-	-
Anti-ice function		-	-	-	-	-	-
Power selector		√	√	√	√	√	√
Eco Function		√	√	√	-	-	-
Remote control		-	√	√	√	√	√
Tilt adjustment		-	-	-	-	-	-
LED indicators		√	√	√	√	√	√
Integrated wi-fi & voice control		-	-	-	√	√	-