

PELER 6C

The air cooler featuring an essential design that's easy to use

Cod. 99310



TOP TO BOTTOM FILLING

The tank doesn't need to be removed from the lower part



TOUCHSCREEN DISPLAY

Touch-screen control panel, with minimal aesthetic impact, for immediate control.



INTEGRATED IONIZER

By negatively charging the air, allows the oxygen molecules to stick to the harmful particles and fall to the ground, reducing the risk of inhaling them.



INTEGRATED TIMER





Automatic shut-down programmable up to 12 hrs


FEATURES

- Maximum power consumption: 75W
- Air flow rate (maximum): 450 m³/h
- Air speed (maximum): 8.5 m/s
- Maximum sound power level: 62 dB(A)
- Filling from top or bottom
- Touch screen display: LED touchscreen display and controls
- 3 operating modes (normal, natural, standby)
- 3 fan speeds (low, medium, high)
- Large removable water tank (up to 6 litres)
- Integrated ioniser
- Purification with air filter and honeycomb evaporative panel
- Timer 1-12 h
- Antidust filter
- Horizontal air flow oscillation mode
- Manual adjustment of vertical flaps
- User-friendly remote control included
- Compact design
- Wheels for easy transportation
- Ice box included



Evaporative coolers

		PELER 4D	PELER 6C	PELER 10 WIFI	PELER 20
PRODUCT CODE		99308	99310	99242	99355
EAN CODE		8021183993080	8021183993103	8021183992427	8021183993554
Electrical power supply	V/F/Hz	220-240 /1/50 - 60	220-240/1/50-60	220-240/1/50-60	220-240/1/50
Maximum power absorption	W	75	75	60	110
Stand-by power consumption	W	-	0,4	≤1	0,45
Fan speed	n	3	3	3	4
Air flow rate (maximum)	m³/h	350	450	200	600
Air speed (maximum)	m/s	7	8,5	5	9,0
Sound pressure level (1)	dB(A)	-	50	44	51
Maximum Sound power level (1)	dB(A)	 57	 62	 55	 60
Insulation class		II	II	II	II
Power cable	n / mm²	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75
Water tank capacity	l	4	6,0	10,0	20,0
Evaporative sheet		Honeycomb	Honeycomb	Honeycomb	Honeycomb
Control panel		Touch	Touch	Touch	Touch
Conformity mark		CE	CE	CE	CE
Dimensions (WxHxD)	mm	235 x 610 x 260	260 x 700 x 300	264 x 770 x 270	342 x 897 x 390
Gift box dimensions (WxHxD)	mm	285 x 630 x 310	316 x 792 x 355	337 x 870 x 340	405 x 960 x 440
Weight (without packaging)	kg	4,5	6,6	6,8	8,0
Weight (with packaging)	kg	5,5	7,6	8,0	10,5
Timer		✓	✓	✓	✓
Removable water tank		✓	✓	✓	✓
Oscillating function		✓	✓	✓	✓
Remote control		✓	✓	✓	✓
Ionizer		-	✓	-	-
Power off switch		-	-	✓	✓
Power supply cable housing		-	-	-	✓

		PELER TOWER
PRODUCT CODE		99312
EAN CODE		8021183993127
Electrical power supply	V/F/Hz	220-240/1/50
Maximum power absorption	W	65
Stand-by power consumption	W	-
Fan speed	n	3
Air flow rate (maximum)	m³/h	300
Air speed (maximum)	m/s	6
Sound pressure level (1)	dB(A)	50-52
Maximum Sound power level (1)	dB(A)	 64
Insulation class		II
Power cable	n / mm²	2 x 0,75
Water tank capacity	l	3,5
Evaporative sheet		Honeycomb
Control panel		Touch
Conformity mark		CE
Dimensions (WxHxD)	mm	320 x 1100 x 320
Gift box dimensions (WxHxD)	mm	245 x 1125 x 230
Weight (without packaging)	kg	5,0
Weight (with packaging)	kg	6,0
Timer		✓
Removable water tank		-
Oscillating function		✓
Remote control		✓
Ionizer		✓
Power off switch		-
Power supply cable housing		-

(1) Test conditions: the sound pressure was measured in a semi-anechoic chamber at a distance of 2 metres from the front part of the appliance (at a distance of 1 metre for code 99242) with the microphone at a height of 1 metre. During measurement, all device functions are enabled except swing (if present).